



GUANGDONG BOSHUN BELTING CO.,LTD.

博力顺
BO LI SHUN

Product Data Sheet

Type: 12U22-24/0A

Main industry segments
Food

Applications
knife edge conveying

Color code
RAL 9003



Product structure	
Top cover	
-Thickness	0.2 mm
-Material	Polyurethane (PU)
-Features	Matt
-Color	White
-Surface	Non adhesive surface
-Hardness	86° ShoreA
Bottom cover	
-Thickness	0.4 mm
-Material	Polyester monofilament impregnated PU
-Features	Lateral stability, Antistatic
-Color	Transparent
-Surface	Rigid fabric
-Hardness	-

Technical data	
Total thickness	1.2 mm
Number of plies	2
Weight	1.4 kg/m ²
Maximum width	3000 mm
Effective pull at 1% elongation	6 N/mm
Twisting force	9.6 N/mm
Maximum admissible tension	11
Breaking strength	110
Temperature range	-20 °C ~ +80 °C

Minimum roll diameter	
Normal flexion	6 mm
Counter flexion	12 mm

Characteristic			
Slide	Yes	Flame retardant	No
Roller	Yes	Cold resistant	No
Trough	No	Knife edges	Yes
Antistatic	No	Curves	No
Oil and fat resistant	Yes	Guides	Yes
FDA	Yes	Cleats	Yes
Low noise	No	Sidewalls	Yes

Product photos



Joining methods

One finger

Disclaimer

All data are approximate values and defined under the following standard climatic conditions.
23 °C, 50 % relative humidity (ISO 554).

All informations are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Boshun Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences

Issued: 2019.04.22

Last update: 2019.04.22